# L/F900 Diagnostic smoke leak finder





### **Find Leaks in:**

- Intake/induction systems
- Exhaust systems
- Turbo systems
- EVAP systems
- EGR systems
- Manifolds
- Seals / gaskets /fittings
- Hoses / lines
- Wind & water leaks
  - . And much more

## Find Leaks with Smoke and Dye Most leaks found in less than 5 minutes!!

The  $TECNOMOTOR^{\circ}$  DIAGNOSTIC SMOKE LEAK FINDER is a full featured device allowing today's workshop to perform a whole range of vehicle leak testing.







Made in Italy 🖊

# L/F900 Diagnostic smoke leak finder

- Eliminate comebacks.
- ➤ Find leaks quickly with smoke and dye. Most leaks found in less than 5 minutes.
- Includes Diagnostic Smoke® technology mandated by auto manufactures in 41 countries.
- > One button operation.
- > Flow meter measures leak size.
- > Vacuum / pressure decay gauge measure leak rate.
- Smoke volume control tunes the right volume for every job.
- "TEST" feature for testing with gas only (no smoke).
- > Enough solution for hundreds of tests.

#### **TECHNICAL SPECIFICATIONS**

|   | Dimensions:                           | H - 23cm x W - 34cm x L- 22.5cm |
|---|---------------------------------------|---------------------------------|
|   | Weight:                               | 6,8 kg (15 lbs)                 |
|   | Power:                                | 12 Volt DC                      |
|   | Inlet pressure:                       | 3.4 to 12 bar (50 to 175 psi)   |
|   | Output pressure:                      | 3.5 kPa   14 in H20             |
|   | Flow rate:                            | 12 LPM                          |
| - | Advanced microprocessor controlled.   |                                 |
|   | Use w/ any inert gas or workshop air. |                                 |

#### **KIT CONTENTS**

| A >        | Accessories Storage Case.                                 |  |
|------------|---|--|
|            | The (2) bottles of UltraTraceUV® smoke solution included  |  |
| <b>B</b> > | performs (500) stan-dard,                                 |  |
|            | 5 minute test cycles                                      |  |
| C >        | Combination white/UV light helps find exiting smoke and   |  |
| 6>         | UV trace at exact leak locations                          |  |
| Π.         | Diffuser unit permits testing for wind and water leaks in |  |
| D >        | vehicle passenger compartments                            |  |
| E >        | Standard adaptor cone                                     |  |
| F>         | Cap Plug Kit  |  |
| G >        | Glasses   |  |







### WWW.TE<u>CNOMOTOR.IT</u>

Cod. DPTCM000031C

NEXION SPA - 11ALY - Società unipersonale soggetta direzione e coordinamento di Minio srl - A sole shareholder Minio company